



ROTAX° ENGINE	900 ACE
Engine details	Liquid-cooled, four-stroke D.O dry sump
Cylinders	3

Engine details	Liquid-cooled, four-stroke D.O.H.C., dry sump
Cylinders	3
Displacement	899.0 cc
Bore	74 mm
Stroke	69.7 mm
Maximum engine speed	7250 RPM
Carburation	EFI
Recommended fuel type	Unleaded
Minimum octane	95
Fuel tank	40 liters

**COLOUR** 



#### **DIMENSIONS**

Vehicle overall length	3280 mm
Vehicle overall width	1180 mm
Vehicle overall height	1430 mm
Ski stance	996 (+/- 21) mm
Track nominal width	600 mm
Track nominal length	3968 mm
Track profile height	32 mm

### **POWERTRAIN**

Drive clutch type	eDrive II
Driven clutch type	QRS SS
Small sprocket number of teeth	1st gear = 3.86:1
Large sprocket number of teeth	2nd gear = 2.3:1
Drive sprocket	7
Brake system	Hydraulic brake with braided steel brake line, plastic master cylinder

## **SUSPENSION**

Front suspension	A-LFS+ with bended lower A-Arms
Front shock	HPG 36
Rear suspension	PPS-6900-A
Center shock	HPG 25
Rear shock	HPG 36

# **FEATURES**

Frame	L-XU
Skis	Blade XC
Seating	Modular, 1-up heated
Handlebar	U-type steel with hooks, mountain strap
Riser block height	Adjustable 130-205 mm
Starter	Electric
Reverse	Mechanical (2F-N-R)

Heated throttle lever	Standard
Heated grips	Standard
Gauge	Analog with display
Mirrors	Standard
Windshield	High (510 mm), one piece
Hitch	Standard
Visor Plug front / rear	Front
12V power outlet	Front



