

# 2020

# RENEGADE® SPORT REV® Gen4 **NEW**

## PACKAGE HIGHLIGHTS

- Rotax® 600 ACE™ engine with 420W magneto
- REV® Gen4 platform with wide-design bodywork
- SC™-5M rear suspension
- 381 x 3487 x 31,8 mm (15 x 137 x 1.25 in.) Cobra® track
- HPG™ rear shock
- Brembo brake with braided stainless-steel brake line
- Ergo-Step side panels
- U-shaped aluminum handlebar with integrated J-hooks
- RAS™ 3 front suspension
- 4.5-in. digital display
- Performance trail seat
- Low windshield with air deflectors
- Standard electric start
- D.E.S.S.™ key



RENEGADE® SPORT 600 ACE™ shown

## ROTAX® ENGINE

### 600 ACE™

Engine details	Liquid-cooled, four-stroke D.O.H.C., dry sump
Cylinders	2
Displacement	600 cc
Bore	74 mm
Stroke	69.7 mm
Maximum engine speed	7,250 RPM
Carburation	EFI
Recommended fuel type	Unleaded
Minimum octane	95
Fuel tank	<b>36 L</b>
Oil tank capacity	2.1 L

## POWERTRAIN

Drive clutch type	eDrive™ II
Driven clutch type	QRS
Engagement	2,200 RPM
Small sprocket number of teeth	21
Large sprocket number of teeth	<b>51</b>
Drive sprocket number of teeth	8
Drive sprocket diameter	183 mm
Brake system	Brembo brake with stainless-steel braided brake line

## FEATURES

Frame	<b>REV® Gen4</b>
Bodywork	<b>Wide design</b>
Skis	Pilot™ DS 2
Seating	<b>Trail Performance</b>
Handlebar	<b>U-shaped aluminum with J-hooks</b>

Riser block height	<b>120 mm</b>
Starter	Electric
Reverse	Mechanical
Heated throttle lever/ grips	Standard
Gauge	<b>4.5-in. digital display</b>

Mirrors	Optional
Windshield	<b>360 mm</b>
Runner	Square 3/8
Carbide configuration	102 mm at 90°
Hitch	Optional

## COLOR

Catalyst Grey / Black

## DIMENSIONS

Vehicle overall length	3,038 mm
Vehicle overall width	1,217 mm
Vehicle overall height	1,267 mm
Ski stance	1,077 mm
Ski overall length	1,066 mm
Track nominal width	381 mm
Track nominal length	3,487 mm
Track profile height	31.8 mm Cobra

## SUSPENSION

Front suspension	<b>RAS™ 3</b>
Front shock	Motion Control
Front suspension max. travel	220 mm
Rear suspension	SC™-5M
Center shock	Motion Control
Rear shock	HPG™
Rear suspension max. travel	245 mm



RENEGADE® SPORT 600 ACE™ shown



RENEGADE® SPORT 600 ACE™ shown

## FEATURE HIGHLIGHTS




### Finger throttle position

Throttle block can be rotated to be used as either a traditional thumb throttle or unique finger throttle.



### iTC™ with ECO® mode

Intelligent Throttle Control (iTC™) throttle-by-wire technology includes three shift-on-the-fly driving modes (Sport, Standard, ECO®).



### 1.25 in. Cobra track

Excellent traction in all conditions; light weight.



### Rotax® engine 600 ACE™

This 62-hp in-line twin EFI 4-stroke is the most fuel-efficient snowmobile engine ever produced.



### 4.5-in. digital display

All-digital LCD gauge cluster with flatter viewing angle for an easy-to-read info center whether standing or sitting.

## GAUGE FEATURES

Speedometer	Standard
Tachometer	Standard
Fuel	Standard
Engine temperature	<b>Standard</b>