

ROTAX° ENGINE	600R E-TEC
Engine details	Liquid-cooled, 3-D R.A.V.E.™
Cylinders	2
Displacement	599.4 cc
Bore	72,3 mm
Stroke	73 mm
Maximum engine speed	8100 RPM
Carburation	Electronic Direct Injection
Recommended fuel type	Unleaded
Minimum octane	95
Fuel tank	37 liters
Oil tank capacity (2-stroke)	3.4 liters

DIMENSIONS	
Vehicle overall length	3190 mm
ehicle overall width	1180 mm
ehicle overall height	1300 mm
Ski stance	996 +/- 21 mm
rack nominal width	406 mm
Frack nominal length	3705 mm
Track profile height	51 mm PowderMax

Black/Grey

POWERTRAIN

2121

Drive clutch type	pDrive with clickers
Driven clutch type	QRS
Brake system	Hydraulic brake with braided steel brake line, plastic master cylinder

SUSPENSION

COLOUR

Front suspension	LFS
Front shock	HPG 36
Rear suspension	PPS²-DS-3700
Center shock	HPG 36
Rear shock	HPG 36

FEATURES

Frame	Radien
Skis	Blade XC
Seating	Sport, 1-up
Handlebar	U-type aluminium with hooks, low mountain strap
Riser block height	140 mm
Starter	Manual, Electric (BYR Opt.)
Reverse	RER
Heated throttle lever	Standard

Heated grips	Standard
Gauge	4.5-in. digital display
Mirrors	-
Windshield	Medium with side deflectors
Hitch	Accessory
Visor Plug front / rear	Front
12V power outlet	Yes, in glove box



