

ROTAX° ENGINE	600R E-TEC
Engine details	Liquid-cooled, 3-D R.A.V.E.™
Cylinders	2
Displacement	599.4 cc
Bore	72,3 mm
Stroke	73 mm
Maximum engine speed	8100 RPM
Carburation	Electronic Direct Injection
Recommended fuel type	Unleaded
Minimum octane	95
uel tank	37 liters
Oil tank capacity (2-stroke)	3.4 liters

<i>DIMENSIONS</i>	
ehicle overall length	3310 mm
/ehicle overall width	1180 mm
ehicle overall height	1300 mm
ski stance	996 +/- 21 mm
rack nominal width	406 mm
rack nominal length	3923 mm
Frack profile height	51 mm PowderMax

Black/Grey

## **POWERTRAIN**

2121

Drive clutch type	pDrive with clickers
Driven clutch type	QRS
Brake system	Hydraulic brake with braided steel brake line, plastic master cylinder

## SUSPENSION

**COLOUR** 

Front suspension	LFS
Front shock	HPG 36
Rear suspension	PPS <sup>2</sup> -DS-3900
Center shock	HPG 36
Rear shock	HPG 36

## **FEATURES**

Frame	Radien
Skis	Blade XC
Seating	Sport, 1-up
Handlebar	U-type aluminium with hooks, low mountain strap
Riser block height	140 mm
Starter	Manual, Electric (BYR Opt.)
Reverse	RER
Heated throttle lever	Standard

Heated grips	Standard
Gauge	4.5-in. digital display
Mirrors	-
Windshield	Medium with side deflectors
Hitch	Accessory
Visor Plug front / rear	Front
12V power outlet	Yes, in glove box



