

XTERRAIN RE 3900

2020



ROTAX® ENGINE

600R E-TEC

850 E-TEC

| | | |
|------------------------------|------------------------------|---|
| Engine details | Liquid-cooled, 3-D R.A.V.E.™ | |
| Cylinders | 2 | |
| Displacement | 599.4 cc | 849 cc |
| Bore | 72,3 mm | 82 mm |
| Stroke | 73 mm | 80.4 mm |
| Maximum engine speed | 8100 RPM | 7900 RPM |
| Carburation | Electronic Direct Injection | Electronic Direct Injection with additional booster injectors |
| Recommended fuel type | Unleaded | |
| Minimum octane | 95 | |
| Fuel tank | 37 liters | |
| Oil tank capacity (2-stroke) | 3,4 liters | |

POWERTRAIN

| | |
|--------------------|--|
| Drive clutch type | pDrive with clickers |
| Driven clutch type | QRS |
| Brake system | Hydraulic brake with braided steel brake line, plastic master cylinder |

FEATURES

| | |
|-----------------------|---|
| Frame | Radien |
| Skis | Blade XC |
| Seating | Sport, 1-up |
| Handlebar | U-type aluminium with hooks, low mountain strap |
| Riser block height | 120 mm |
| Starter | Manual, Electric |
| Reverse | RER |
| Heated throttle lever | Standard |

COLOUR

 Manta Green/Grey

DIMENSIONS

| | |
|------------------------|-----------------|
| Vehicle overall length | 3310 mm |
| Vehicle overall width | 1180 mm |
| Vehicle overall height | 1230 mm |
| Ski stance | 996 +/- 21 mm |
| Track nominal width | 406 mm |
| Track nominal length | 3923 mm |
| Track profile height | 51 mm PowderMax |

SUSPENSION

| | |
|------------------|------------------------|
| Front suspension | LFS |
| Front shock | KYB 40 HLCR Kashima |
| Rear suspension | PPS ² -3900 |
| Center shock | KYB 46 HLCR Kashima |
| Rear shock | KYB 46 HLCR Kashima |

| | |
|-------------------------|------------------------------|
| Heated grips | Standard |
| Gauge | 7.2-in. wide digital display |
| Mirrors | - |
| Windshield | Low |
| Hitch | Accessory |
| Visor Plug front / rear | Front |
| 12V power outlet | Yes, in glove box |