™ MAVERICK DS TURBO R

HIGHLIGHTS

PLATFORM FEATURES

- 163 cm wide
- 260 cm wheelbase
- 36 cm of ground clearance
- High torque Dynamic Power Steering (DPS™)
- 51 cm suspension travel
- FOX† 2.5 PODIUM† QS3 Piggyback shocks
- 14-in. aluminum wheels
- 28-in. Maxxis† Bighorn 2.0† tires
- 4.5-in. digital display
- · Rear tow hook

DEFIANT

Type

- Trademark Can-Am DNA with next generation design
- Low seating position Ergo-Lok cockpit with four-
- way adjustable seats

POWERFUL

- 172 hp turbocharged and intercooled Rotax® ACE
- Advanced airflow dynamics
- QRS-X transmission

PRECISE

172 hp, Rotax ACE (Advanced Combustion Efficiency) 900 cc

Turbocharged Triple-cylinder engine, liquid cooled with integrated intercooler and high-performance air filter

Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI) Quick Response System X (QRS-X) CVT with high airflow, L/H/N/R/P

> Selectable 2WD / 4WD with Visco-Lok[‡] auto-locking front differential

> High torque Tri-Mode Dynamic Power Steering (DPS)

- TTX suspension with industry leading travel
- Ultra efficient and lightweight chassis
- Sharpest handling features

SPECIFIC TO DS PACKAGE • 172 hp Turbo R engine



Can-Am Red & White / TURBO R

IIKE9/	WHEELS
Front Tires	

Front Tires	Maxxis Bighorn 2.0 28 x 9 x 14 in. (71.1 x 22.9 x 35.6 cm)
Rear Tires	Maxxis Bighorn 2.0 28 x 11 x 14 in. (71.1 x 27.9 x 35.6 cm)
Wheels	14-in. (35.6 cm) cast-aluminum

USPENSIO

Fuel Delivery System

Transmission Drive Train

Power Steering

COOL EMOIONO	
Front Suspension	Double A-arm with sway bar / 20 in. (50.8 cm) travel
Front Shocks	FOX 2.5 PODIUM Piggyback with QS3 compression adjustment
Rear Suspension	4-link Torsional Trailing-arm X (TTX) with sway bar 50.8 cm travel
Rear Shocks	FOX 2.5 PODIUM Piggyback with QS3 compression adjustment and

BRAKES	
Front	Dual 262 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Dual 248 mm ventilated disc brakes with hydraulic twin-piston calipers

DIIVIENSIUNS / CAPACITIES	
LxWxH	132 x 64 x 65.4 in. (335.3 x 162.5 x 166.1 cm)
Wheelbase	259.1 cm
Ground Clearance	35.6 cm
Estimated Dry Weight	671.9 kg
Chassis / Cage	Dual-phase 980 steel
Rack Capacity	91 kg with LinQ™ quick-attach
Storage Capacity	Total: 9.4 L Glove box: 6.2 L Center console: 2.8 L Cup holders: 0.4 L
Fuel Capacity	40 L

Gauge	4.5 in. (11.4 cm) wide digital display with keypad: Speedometer, tachometer, odometer, trip and hour	Protection
	meters, fuel, gear position, SPORT / ECO™ mode, seat belt and 4 x 4 indicator, diagnostics, clock, auto shut off	Instrumentati
		Lighting
Winch	Ν/Δ	Anti-theft Svs

Protection	Integrated front bumper, quarter-doors, HMWPE full skid plate, rear tow hook
Instrumentation	Lighter type DC outlet in central console
Lighting	LED headlights and tail lights
Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™) with

Factory 2 years

©2019 Bombardier Recreational Products Inc. (BRP), All rights reserved. TM, ® and the BRP logo are trademarks of Bombardier Recreational Products Inc. or its affiliates. In the U.S.A., the products are distributed by BRP US Inc. "Visco-Lok is a trademark of GKN Viscodrive GmbH. "All other trademarks are the property of their respective owners. BRP reserves the right, at any time, to discontinue or change specifications, prices, designs, features, models or equipment without incurring obligation. Some models depicted may include optional equipment. Read the side-by-side vehicle (SSV) Operator's Guide and watch the Safety DVD before driving. For your safety: wear a helmet, eye protection and other protective gear. Fasten lateral net and seat belt at all times. Always remember that riding and alcohol/drugs don't mix. SSV is for off-road use only. Never ride on paved surfaces or public roads. Operator must be at least 16 years old. Passenger must be at least 12 years old and able to hold handgrips and plant feet while seated against the backrest. Never engage in stunt driving and avaid excessive speed driving and avoid excessive speed

