RENEGADE X° mr 1000R

HIGHLIGHTS

- Rotax® snorkeled V-Twin engine with relocated
 CVT intake and outlet
- Intelligent Throttle Control (iTC[™]) with riding modes
- Front and rear FOX[†] PODIUM[†] 1.5 QS3
- 30-in. ITP Cryptid[†] tires
- 14-in. cast-aluminum beadlock wheels
- 3,000-lb (1,361 kg) WARN† winch with roller fairlead
- Front & central aluminum skid plate
- Heavy-duty front and rear bumpers
- Continuously Variable Transmission (CVT) with Extra Low L-Gear
- Aluminum taper-profile handlebar with grab handle, wind deflectors ans square pad
- Tri-Mode Dynamic Power Steering (DPS™)

- Torsional Trailing arm Independent (TTI) rear suspension
- Mudguards
- Multifunction digital gauge
- Painted plastics for premium look
- X-package coloration, graphics and seat cover



Black & Platinum Silver

ENGINE	1000R
Туре	91 hp, Rotax 976 cc V-twin, snorkeled, liquid cooled
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	CVT, P / R / N / H / Extra Low L, standard engine braking
Drive Train	Selectable 2WD / 4WD with Visco-Lok QE [‡] auto-locking front differential
Power Steering	Tri-Mode Dynamic Power Steering (DPS)

SUSPENSIONS	
Front Suspension	Arched double A-arm with front sway bar
Front Shocks	FOX [†] PODIUM [†] 1.5 QS3
Rear Suspension	Torsional Trailing arm Independent (TTI)
Rear Shocks	FOX [†] PODIUM [†] 1.5 QS3

BRAKES	
Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Single 214 mm ventilated disc brake with hydraulic twin-piston caliper

TIRES / WHEELS	
Front Tires	ITP Cryptid†
	30 x 9 x 14 in.
	(76.6 x 22.9 x 35.6 cm)
Rear Tires	ITP Cryptid†
	30 x 9 x 14 in.
	(76.6 x 22.9 x 35.6 cm)
Wheels	14-in_cast-aluminum headlock

DIMENSIONS / CAPACITIES				
LxWxH	224 x 127 x 131 cm			
Wheelbase	129.5 cm			
Ground Clearance	31.8 cm			
Seat Height	93.3 cm			
Dry Weight	450 kg			
Rack Capacity	Rear: 16 kg			
Storage Capacity	N/A			
Towing Capacity	590 kg			
Fuel Capacity	20.5 L			

FEATURES			
Gauge	Multifunction Digital: Speedometer, tachometer, odometer, trip & hour meters, fuel, gear position, 4 x 4 indicator, diagnostics, clock	Instrumentation	Lighter type DC outlet in console, standard connector in the back (15-A)
		Lighting	240 W from 4 fender mounted projector beam headlamps (60 W) with tail light / brake light
		Seat	Standard
Winch	3,000-lb (1,361 kg) WARN winch with roller fairlead	Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™)
Protection	Front & rear bumpers Aluminum taper-profile handlebar with grab handle, wind deflectors and square pad Mudguards front & central aluminum skid plate		

WARRANTY		
Factory	2 years	

